



NOTE

1. THIS DRAWING SUPPLEMENTAL TO OPSD 404.020 AND 404.022
2. ALUMINUM TO BE OF APPROVED ALLOY. AT ALL POINTS WHERE ALUMINUM AND CONCRETE COME INTO CONTACT (ENDS OF ANGLES) ALUMINUM SURFACES TO BE COATED WITH ZINC CHROMATE OR TWO COATS OF STATIC ASPHALT PAINT.
3. PLATFORMS MUST BE USED FOR MAINTENANCE HOLE DEPTHS GREATER THAN 5m. FOR MAINTENANCE HOLE DEPTH BETWEEN 5m AND 10m, PLATFORM TO BE PLACED AT MIDPOINT. FOR MAINTENANCE HOLE DEPTH BETWEEN 10m AND 15m, PLATFORMS TO BE PLACED AT THIRD POINTS.
4. ALTERNATE TO CHAIN IS SELF LOCKING GATE.
5. WHERE PLATFORMS ARE REQUIRED, INSIDE DIAMETER OF CHAMBER TO BE MIN. 1500mm



**PUBLIC WORKS
STANDARD DRAWING**

REV. DATE: NOVEMBER 2011

APPROVED BY

DRAWN BY

A.P.

AINLEY GROUP

STD. DWG. NUMBER

SCALE

1-2-1

N.T.S.

**SAFETY PLATFORM
FOR 1500mm DIAMETER PRECAST MAINTENANCE HOLE**