



DELETED
REFER TO SECTION 2.6

NOTE

1. ALUMINUM TO BE OF APPROVED ALLOY. AT ALL POINTS WHERE ALUMINUM AND CONCRETE COME INTO CONTACT (ENDS OF ANGLES) ALUMINUM SURFACES TO BE COATED WITH ZINC CHROMATE OR TWO COATS OF STATIC ASPHALT PAINT.
2. PLATFORM MUST BE USED FOR MAINTENANCE HOLE DEPTHS GREATER THAN 5m. PLATFORM TO BE PLACED AT 2m FROM TOP COVER.
3. DROP STRUCTURES TO BE LOCATED BELOW SAFETY PLATFORM.
4. WHERE OBVERT OF DROP PIPE TO CENTRELINE OF SEWER PIPE EXCEEDS 1500mm, SAFETY PLATFORM TO BE INSTALLED AT 1m BELOW CENTRELINE SEWER PIPE OPENING.
5. TOP SAFETY PLATFORM TO BE PLACED AT MAX 2m FROM TOP COVER & TO REMAIN IN THE CLOSED (DOWN) POSITION.
6. BOTTOM SAFETY PLATFORM TO REMAIN IN THE OPEN (UP) POSITION.



**PUBLIC WORKS
STANDARD DRAWING**

REV. DATE: DECEMBER 2013

REVISION NUMBER: FOR REVISION TRACKING REFER TO STD. DWG. 2-0-2

APPROVED BY DRAWN BY

R.D.T. L.W.

STD. DWG. NUMBER SCALE

2-2-1 N.T.S.

**SAFETY PLATFORM FOR 1200mm
DIAMETER PRECAST MAINTENANCE HOLE**