

19/C (VEH.)

1. R1 - M.S. RED
2. R2 - S.S. RED
3. R3 - M.S. L.T. RED (PROT)
4. R4 - S.S. L.T. RED (PROT)
5. R5 - M.S. BIKE RED
6. Y1 - M.S. AMBER
7. Y2 - S.S. AMBER
8. Y3 - M.S. L.T. AMBER (PROT)
9. Y4 - S.S. L.T. AMBER (PROT)
10. Y5 - M.S. BIKE AMBER
11. BL1 - M.S. GREEN
12. BL2 - S.S. GREEN
13. BL3 - M.S. L.T. GREEN ARROW (PROT)
14. BL4 - S.S. L.T. GREEN ARROW (PROT)
15. BL5 - M.S. BIKE GREEN
16. W1 - M.S. NEUTRAL
17. W2 - S.S. NEUTRAL
18. BLK - SPARE
19. O - SPARE

12/C (PED)

- R1 - M.S. D.W.
- R2 - S.S. D.W.
- R3 - S.S. BIKE RED
- Y1 - S.S. P.B. (+)
- Y2 - S.S. P.B. (-)
- Y3 - S.S. BIKE AMBER
- BL1 - M.S. W.
- BL2 - S.S. W.
- BL3 - S.S. BIKE GREEN
- W - NEUTRAL
- BLK - M.S. P.B. (+)
- O - M.S. P.B. (-)

NOTE

1. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH DRAWINGS IN 4-3-2 AND 4-3-1-A

ALL DIMENSIONS IN MILLIMETRES
UNLESS OTHERWISE NOTED



PUBLIC WORKS
STANDARD DRAWING

REV. DATE: DECEMBER 2018

APPROVED BY

GK

STD. DWG. NUMBER

4-3-3-A

DRAWN BY

TSS SECTION

SCALE

N.T.S.

TRAFFIC SIGNAL CONDUCTOR DESIGNATION
(19/C AND 12/C) - 2 GROUP CONFIGURATION