

HORIZONTAL SINGLE MEMBER ARM FOR SIGNS (6063T-6 ALUMINUM) WITH 6TR-78 POLE PLATE (2 RISE) (LENGTH AS PER SIGNAL DRAWING)

OCTAGONAL POLE

BAND-IT 1 BOLT BRACK-ITS & LOCK-TITE BAND (TYPICAL)

Rb-41  
60x60

Rb-41  
60x60

Rb-39  
90X150

Rb-61A  
90X150

LOCK-TITE BAND OR BAND-IT BAND

8mm x 65mm CARRIAGE BOLT WITH WASHER AND 2-NUTS

8mm x 32mm GALV. BOLT WITH NUT

ALUMINUM STREET SIGN

18mm O.D. GALV. LOCK WASHER 2mm THICK (TYP.)

**SECTION A-A**

10mm SQ. HOLES

56mm

28mm O.C.

10mmx22mm OVAL HOLES

70mm

40mm

40mm

115mm

10x20mm OVAL HOLE

**FRONT VIEW**

**NOTES**

1. POLE PLATE BOLTS TO BE ADJUSTED SO THAT HORIZONTAL PORTION OF ARM IS LEVEL
2. MOUNTING HOLES FOR BRACKET & SIGN TO BE FIELD DRILLED
3. PLACE APPROXIMATE 5° VERTICAL TILT ON SIGN

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.



**PUBLIC WORKS  
STANDARD DRAWING**

REV. DATE: FEBRUARY 2015

APPROVED BY

DRAWN BY

G.K./S.L.

O.A.

STD. DWG. NUMBER

SCALE

**4-6-2**

N.T.S.

**OVERHEAD LANE CONTROL  
SIGN SUPPORT**