



NOTES

1. THIS DRAWING MUST BE USED IN CONJUNCTION WITH STANDARD DRAWING 5-2-6, 5-2-9A AND 5-2-9B
2. EXPANSION JOINT FILLER SHALL CONSIST OF BITUMINOUS FIBRE MATERIAL ABUTTING ALL RIGID OBJECTS OF OTHER CONCRETE WORKS INCLUDING UTILITY POLES, POLE BASES, MAINTENANCE HOLES ETC
3. SAW CUTS SHALL BE 1/3 THE DEPTH IN DIAMOND PATTERN (DIAGONAL) WITH 600mm X 600mm SQUARES
4. UNIFORM COARSE TEXTURED SWIRL FINISH SHALL BE APPLIED TO ALL CHANNELIZED ISLAND INFILLS
5. COLOUR:
 MISSISSAUGA: NATURAL CONCRETE COLOUR, NO COLOUR ADDITIVE
 BRAMPTON: COLOURED CONCRETE SHALL BE "BRAMPTON HERITAGE" PIGMENT, BY QC CONSTRUCTION PRODUCTS OR APPROVED EQUIVALENT
 CALEDON: COLOURED CONCRETE/ASPHALT SHALL BE "BOLTON RED" PIGMENT

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.



**PUBLIC WORKS
STANDARD DRAWING**

REV. DATE: MARCH 2017

APPROVED BY

DRAWN BY

G.K./S.L.

G.K.

**CHANNELIZED CONCRETE ISLAND
REQUIREMENTS**

STD. DWG. NUMBER

SCALE

5-2-11

N.T.S.