



NOTES

1. PLANTING SOIL MIXTURE SHALL CONFORM TO PEEL REGION SPECIFICATION FOR PREPARATION AND INSTALLATION OF TREE PLANTING SOIL.
2. SUBGRADE SOIL TO BE TILLED TO A DEPTH OF 25-50mm PRIOR TO INSTALLING PLANTING SOIL.
3. 25-50mm OF PLANTING SOIL SHALL BE PLACED IN THE TRENCH AND TILLED INTO THE SUBGRADE SOIL.
4. REMAINING PLANTING SOIL SHALL BE INSTALLED IN LIFTS OF 150mm-300mm AND COMPACTED BETWEEN 75% AND 80% OF MAXIMUM DRY DENSITY (PROCTOR).
5. TILL 40mm OF ORGANIC MATTER (COMPOST) INTO TOP LAYER OF INSTALLED PLANTING SOIL TO A DEPTH OF 60-90mm.



**PUBLIC WORKS
STANDARD DRAWING**

DATE: AUGUST 2016

APPROVED BY

DRAWN BY

G.K./B.N.

C.B.

STD. DWG. NUMBER

SCALE

5-4-13

N.T.S.

**BOULEVARD TREE PLANTING
SOIL TRENCH FOR SOFTSCAPE BOULEVARDS
(RETROFIT)**